

Compact Cylinder ADVU-125-25-P-A - Festo 175753

Item no.	FES-175753	Manufacturer	Festo
Manufacturer no.	ADVU-125-25-P-A	EAN	4052568143268

Festo pneumatic cylinder for precise linear motion and defined force in automation.

TECHNICAL DATA



Article authenticity	Original product
Betriebsdruck max [bar]	10.000000
Bohrung (mm)	125.000000
Condition of article	New
HS-Code	84123100
Hub [mm]	25.000000
Pneumatischer Anschluss	G1/4
Weight	3.426 kg

STANDARDS & COMPLIANCE

ISO 8573-1:2010

DESCRIPTION

Festo pneumatic cylinder for precise linear motion and defined force in automation. The key technical data of this genuine Festo article are listed below.

Stroke [mm]	25
Piston diameter	125 mm
Dampening	P: Elastic silencer rings / plates double-sided
installation position	arbitrary
Principle of operation	double acting
Piston rod end	Female thread
Construction set up	Piston piston rod
Position detection	For proximity switch
Variants	One-sided piston rod

Operating pressure [bar]	0.5 to 10
Operating medium	Compressed air to ISO 8573-1:2010 [7:4:4]
Information about operating and control medium	Oiled operation possible (required in further operations)
Corrosion resistant class KBK	2 - moderate corrosion stress
ambient temperature [°C]	-20 to 80
Impact energy at the end positions [J]	3,30
Theoretical force at 6 bar, Return flow [N]	6.881
Theoretical force at 6 bar, flow [N]	7.363
Moving mass at 0 mm stroke [g]	1.317
Weight supplement per 10 mm stroke [g]	168
Base weight at 0 mm stroke [g]	3.426
Supplement moved mass per 10 mm stroke [g]	63
Fastening type	With throughway bores With Accessories Selectively:
Pneumatic connection	G1/4
Flush screw material	Zinc plated steel
Cover material	Aluminium wrought alloy
Dynamic seals material	NBR TPE-U(PU)
Piston rod material	High-alloyed steel
Cylinder tube material	Aluminium wrought alloy