

Compact Cylinder ADVU-32-15-P-A - Festo 156532

Item no. FES-156532

Manufacturer Festo

EAN 4052568117962

Festo pneumatic cylinder for precise linear motion and defined force in automation.

TECHNICAL DATA

Betriebsdruck max [bar]	10.000000
Bohrung (mm)	32.000000
HS-Code	84123100
Hub [mm]	15.000000
Pneumatischer Anschluss	G1/8
Weight	0.37 kg



STANDARDS & COMPLIANCE

ISO 8573-1:2010

DESCRIPTION

Festo pneumatic cylinder for precise linear motion and defined force in automation. The key technical data of this genuine Festo article are listed below.

Stroke [mm]	15
Piston diameter	32 mm
Dampening	P: Elastic silencer rings / plates double-sided
installation position	arbitrary
Principle of operation	double acting
Piston rod end	Female thread
Construction set up	Piston piston rod
Position detection	For proximity switch
Variants	One-sided piston rod
Operating pressure [bar]	0.8 to 10
Operating medium	Compressed air to ISO 8573-1:2010 [7:4:4]

Information about operating and control medium	Oiled operation possible (required in further operations)
Corrosion resistant class KBK	2 - moderate corrosion stress
ambient temperature [°C]	-20 to 80
Impact energy at the end positions [J]	0,40
Theoretical force at 6 bar, Return flow [N]	415
Theoretical force at 6 bar, flow [N]	483
Moving mass at 0 mm stroke [g]	49
Weight supplement per 10 mm stroke [g]	40
Base weight at 0 mm stroke [g]	300
Supplement moved mass per 10 mm stroke [g]	9
Fastening type	With throughway bores With Accessories Selectively:
Pneumatic connection	G1/8
Flush screw material	Zinc plated steel
Cover material	Aluminium wrought alloy
Dynamic seals material	NBR TPE-U(PU)
Piston rod material	High-alloyed stainless steels
Cylinder tube material	Aluminium wrought alloy