

Compact Cylinder AEVU-100-10-A-P-A - Festo 157018

Item no. FES-157018

Manufacturer Festo

EAN 4052568122546

Festo pneumatic cylinder for precise linear motion and defined force in automation.

TECHNICAL DATA

Ausführungstyp	einseitige Kolbenstange
Betriebsdruck max [bar]	10.000000
Bohrung (mm)	100.000000
Corrosion resistance class CRC	2 - moderate corrosion stress
Cushioning	P: Elastic silencer rings / plates double-sided
Design	Piston, piston rod
Funktion	drückend
HS-Code	84123100
Hub [mm]	10.000000
Medium	Druckluft
Mounting position	arbitrary
Pneumatischer Anschluss	G1/4
Position sensing	Yes
Serie	AEVU
Temperature (max.)	80
Weight	3.1 kg



STANDARDS & COMPLIANCE

ISO 8573-1:2010

DESCRIPTION

Festo pneumatic cylinder for precise linear motion and defined force in automation. The key technical data of this genuine Festo article are listed below.

Stroke [mm]	10
Piston diameter	100 mm
Dampening	P: Elastic silencer rings / plates double-sided
installation position	arbitrary
Principle of operation	Pressing single action
Piston rod end	Male thread
Construction set up	Piston piston rod
Position detection	For proximity switch

esd.equipment

Keldersstr. 15

42697 Solingen, Deutschland

VAT ID: DE269659389

Phone: +49 212 38340680

shop@esd-equipment.com

esd.equipment

Page 1/2

Variants	One-sided piston rod
Operating pressure [bar]	0.6 to 10
Operating medium	Compressed air to ISO 8573-1:2010 [7:4:4]
Information about operating and control medium	Oiled operation possible (required in further operations)
Corrosion resistant class KBK	2 - moderate corrosion stress
ambient temperature [°C]	-20 to 80
Impact energy at the end positions [J]	1,00
Theoretical force at 6 bar, flow [N]	4.516
Moving mass at 0 mm stroke [g]	614
Weight supplement per 10 mm stroke [g]	177
Base weight at 0 mm stroke [g]	2.797
Supplement moved mass per 10 mm stroke [g]	38
Fastening type	With throughway bores With Accessories Selectively:
Pneumatic connection	G1/4
Flush screw material	Zinc plated steel
Cover material	Aluminium wrought alloy
Dynamic seals material	NBR TPE-U(PU)
Piston rod material	High-alloyed steel
Cylinder tube material	Aluminium wrought alloy