

Compact Cylinder AEVU-16-25-A-P-A - Festo 156985

Item no. FES-156985

Manufacturer Festo

EAN 4052568122218

Festo pneumatic cylinder for precise linear motion and defined force in automation.

TECHNICAL DATA

Ausführungstyp	einseitige Kolbenstange
Betriebsdruck max [bar]	10.000000
Bore (mm)	16.000000
Corrosion resistance class CRC	2 - moderate corrosion stress
Cushioning	P: Elastic silencer rings / plates double-sided
Design	Piston, piston rod
Funktion	pushing
HS-Code	84123100
Hub [mm]	25
Medium	Compressed air
Mounting position	arbitrary
Operating conditions	ISO 8573-1
Pneumatic connection	M5
Position sensing	Yes
Series	AEVU
Temperature (max.)	80
Weight	0.14 kg



STANDARDS & COMPLIANCE

ISO 8573-1:2010

DESCRIPTION

Festo pneumatic cylinder for precise linear motion and defined force in automation. The key technical data of this genuine Festo article are listed below.

Stroke [mm]	25
Piston diameter	16 mm
Dampening	P: Elastic silencer rings / plates double-sided
installation position	arbitrary
Principle of operation	Pressing single action
Piston rod end	Male thread
Construction set up	Piston piston rod

esd.equipment

Keldersstr. 15

42697 Solingen, Deutschland

VAT ID: DE269659389

Phone: +49 212 38340680

shop@esd-equipment.com

esd.equipment

Page 1/2

Position detection	For proximity switch
Variants	One-sided piston rod
Operating pressure [bar]	1.3 to 10
Operating medium	Compressed air to ISO 8573-1:2010 [7:4:4]
Information about operating and control medium	Oiled operation possible (required in further operations)
Corrosion resistant class KBK	2 - moderate corrosion stress
ambient temperature [°C]	-20 to 80
Impact energy at the end positions [J]	0,10
Theoretical force at 6 bar, flow [N]	111
Moving mass at 0 mm stroke [g]	12
Weight supplement per 10 mm stroke [g]	15
Base weight at 0 mm stroke [g]	89
Supplement moved mass per 10 mm stroke [g]	4
Fastening type	With throughway bores With Accessories Selectively:
Pneumatic connection	M5
Flush screw material	High-alloyed stainless steels
Cover material	Aluminium wrought alloy
Dynamic seals material	NBR TPE-U(PU)
Piston rod material	High-alloyed stainless steels
Cylinder tube material	Aluminium wrought alloy