

Guided Drive DFM-20-40-P-A-KF - Festo 170918

Item no. FES-170918

Manufacturer Festo

EAN 4052568013479

Festo pneumatic cylinder for precise linear motion and defined force in automation.

TECHNICAL DATA

Betriebsdruck max [bar]	10.000000
Bohrung (mm)	20.000000
HS-Code	84123100
Hub [mm]	40.000000
Pneumatischer Anschluss	M5
Weight	1 kg
Werkstoff	Aluminium



STANDARDS & COMPLIANCE

ISO 8573-1:2010

DESCRIPTION

Festo pneumatic cylinder for precise linear motion and defined force in automation. The key technical data of this genuine Festo article are listed below.

Centre of mass distance of payload to Joch plate [mm]	50
Stroke [mm]	40
Piston diameter	20 mm
Operating mode actuator unit	Joch
Dampening	P: Elastic silencer rings / plates double-sided
installation position	arbitrary
Guide	ball guide
Construction set up	Guide
Position detection	For proximity switch
Operating pressure [bar]	2 to 10
Max. speed [m/s]	0,8

esd.equipment

Keldersstr. 15

42697 Solingen, Deutschland

VAT ID: DE269659389

Phone: +49 212 38340680

shop@esd-equipment.com

esd.equipment

Page 1/2

Principle of operation	double acting
Operating medium	Compressed air to ISO 8573-1:2010 [7:4:4]
Information about operating and control medium	Oiled operation possible (required in further operations)
Corrosion resistant class KBK	0 - No corrosion stressing
ambient temperature [°C]	-5 to 60
Impact energy at the end positions [J]	0,200
Max. permitted moment load Mx depending on stroke [Nm]	4,640
Max. usable load depending on the stroke at a defined distance xs [N]	108,00
Theoretical force at 6 bar, Return flow [N]	141
Theoretical force at 6 bar, flow [N]	188
Moving mass [g]	488,0
Product weight [g]	981,0
Alternative connections	See product drawing
Pneumatic connection	M5
Material information	Copper and PTFE-free RoHs compliant
Cover material	Aluminium wrought alloy
Seals material	NBR
Housing material	Aluminium wrought alloy
Piston rod material	High-alloyed stainless steels
Max. force Fy [N]	817
Max. force Fy static [N]	1.020
Max. force Fz [N]	817
Max. force Fz static [N]	1.020
Max. torque Mx [Nm]	23,69
Max. torque Mx static [Nm]	29,58
Max. torque My [Nm]	15,11
Max. torque My static [Nm]	18,87
Max. torque Mz [Nm]	15,11
Max. torque Mz static [Nm]	18,87
Centre of mass of the moved mass depending on stroke [mm]	34,6