

Guided Drive DFM-80-50-P-A-GF - Festo 170886

Item no. FES-170886

Manufacturer Festo

EAN 4052568013400

Festo pneumatic cylinder for precise linear motion and defined force in automation.

TECHNICAL DATA

Betriebsdruck max [bar]	10.000000
Bohrung (mm)	80.000000
HS-Code	84123100
Hub [mm]	50.000000
Pneumatischer Anschluss	G3/8
Weight	8 kg
Werkstoff	Aluminium



STANDARDS & COMPLIANCE

ISO 8573-1:2010

DESCRIPTION

Festo pneumatic cylinder for precise linear motion and defined force in automation. The key technical data of this genuine Festo article are listed below.

Centre of mass distance of payload to Joch plate [mm]	125
Stroke [mm]	50
Piston diameter	80 mm
Operating mode actuator unit	Joch
Dampening	P: Elastic silencer rings / plates double-sided
installation position	arbitrary
Guide	sliding guide
Construction set up	Guide
Position detection	For proximity switch
Operating pressure [bar]	0.5 to 10
Max. speed [m/s]	0,4

esd.equipment

Keldersstr. 15

42697 Solingen, Deutschland

VAT ID: DE269659389

Phone: +49 212 38340680

shop@esd-equipment.com

esd.equipment

Page 1/2

Principle of operation	double acting
Operating medium	Compressed air to ISO 8573-1:2010 [7:4:4]
Information about operating and control medium	Oiled operation possible (required in further operations)
Corrosion resistant class KBK	1 - low corrosion stress
ambient temperature [°C]	-20 to 80
Impact energy at the end positions [J]	0,750
Max. permitted moment load Mx depending on stroke [Nm]	24,200
Max. usable load depending on the stroke at a defined distance xs [N]	311,00
Theoretical force at 6 bar, Return flow [N]	2.827
Theoretical force at 6 bar, flow [N]	3.016
Moving mass [g]	4.717,0
Product weight [g]	8.185,0
Alternative connections	See product drawing
Pneumatic connection	G3/8
Material information	RoHs compliant
Cover material	Aluminium wrought alloy
Seals material	NBR
Housing material	Aluminium wrought alloy
Piston rod material	High-alloyed stainless steels