

Twin-Piston Cylinder DPZ-20-100-P-A-KF - Festo 162066

Item no. FES-162066

Manufacturer Festo

EAN 4052568130091

Festo pneumatic cylinder for precise linear motion and defined force in automation.

TECHNICAL DATA

Betriebsdruck max [bar]	10.000000
Bohrung (mm)	20.000000
HS-Code	84123100
Hub [mm]	100.000000
Pneumatischer Anschluss	M5
Weight	1 kg
Werkstoff	Aluminium



STANDARDS & COMPLIANCE

ISO 8573-1:2010

DESCRIPTION

Festo pneumatic cylinder for precise linear motion and defined force in automation. The key technical data of this genuine Festo article are listed below.

Stroke [mm]	100
Alignable end position range/Length [mm]	10
Piston diameter	20 mm
Operating mode actuator unit	Joch
Dampening	P: Elastic silencer rings / plates double-sided
installation position	arbitrary
Guide	ball guide
Construction set up	Guide
Position detection	For proximity switch
Operating pressure [bar]	1 to 10
Principle of operation	double acting

esd.equipment

Keldersstr. 15
42697 Solingen, Deutschland
VAT ID: DE269659389

Phone: +49 212 38340680
shop@esd-equipment.com

esd.equipment

Page 1/2

Operating medium	Compressed air to ISO 8573-1:2010 [7:4:4]
Information about operating and control medium	Oiled operation possible (required in further operations)
Corrosion resistant class KBK	0 - No corrosion stressing
ambient temperature [°C]	-20 to 80
Impact energy at the end positions [J]	0,20
Theoretical force at 6 bar, Return flow [N]	282
Theoretical force at 6 bar, flow [N]	376
Alternative connections	See product drawing
Pneumatic connection	M5
Cover material	Aluminium wrought alloy
Seals material	NBR
Housing material	Aluminium wrought alloy
Piston rod material	Case-hardening steel