

Semi-Rotary Drive DSR-40-180-P - Festo 13467

Item no. FES-13467

Manufacturer Festo

EAN 4052568002558

Festo rotary actuator for defined swivel motion and positioning in automation.

TECHNICAL DATA

Betriebsdruck max [bar] **8.000000**

HS-Code **84123900**

Pneumatischer Anschluss **G1/4**

Weight **2.5 kg**



STANDARDS & COMPLIANCE

ISO 8573-1:2010

DESCRIPTION

Festo rotary actuator for defined swivel motion and positioning in automation. The key technical data of this genuine Festo article are listed below.

size	40
Dampening angle [deg]	0,9
Settings range swivel angle [deg]	0 to 180
Swivel angle [deg]	0 to 180
Dampening	P: Elastic silencer rings / plates double-sided
installation position	arbitrary
Principle of operation	double acting
Construction set up	Rotary vane
Position detection	without
Operating pressure [bar]	1.5 to 8
Max. swivel frequency at 6 bar [Hz]	3

esd.equipment

Keldersstr. 15
42697 Solingen, Deutschland
VAT ID: DE269659389

Phone: +49 212 38340680
shop@esd-equipment.com

esd.equipment

Page 1/2

Operating medium	Compressed air to ISO 8573-1:2010 [7:-:-]
ambient temperature [°C]	-10 to 60
Theoretical torque at 6 bar [Nm]	20,0
Product weight [g]	2.400
Fastening type	With throughway bores
Pneumatic connection	G1/4
Drive shaft material	Nickel- plated steel
Seals material	NBR