

Flat Cylinder DZF-18-40-A-P-A - Festo 161239

Item no. FES-161239

Manufacturer Festo

EAN 4052568128593

Festo pneumatic cylinder for precise linear motion and defined force in automation.

TECHNICAL DATA

Betriebsdruck max [bar]	10.000000
Bore (mm)	18.000000
Corrosion resistance class CRC	2 - moderate corrosion stress
Cushioning	P: Elastic silencer rings / plates double-sided
Design	Piston, piston rod
Dichtmaterial	NBR, TPE-U(PU)
Funktion	double-acting
HS-Code	84123100
Hub [mm]	40
Material	Aluminium
Medium	Compressed air
Mounting position	arbitrary
Pneumatic connection	M5
Position sensing	Yes
Series	DZF
Temperature (max.)	80
Weight	0.165 kg



STANDARDS & COMPLIANCE

ISO 8573-1:2010

DESCRIPTION

Festo pneumatic cylinder for precise linear motion and defined force in automation. The key technical data of this genuine Festo article are listed below.

Stroke [mm]	40
Piston diameter	18 mm Equivalent diameter
Max. twist angle of the piston rod $\pm$ [deg]	1,2
Dampening	P: Elastic silencer rings / plates double-sided
installation position	arbitrary
Principle of operation	double acting
Construction set up	Piston piston rod

esd.equipment

Keldersstr. 15

42697 Solingen, Deutschland

VAT ID: DE269659389

Phone: +49 212 38340680

shop@esd-equipment.com

esd.equipment

Page 1/2

Position detection	For proximity switch
Anti-twist lock / guide	Oval piston
Operating pressure [bar]	1 to 10
Operating medium	Compressed air to ISO 8573-1:2010 [7:4:4]
Information about operating and control medium	Oiled operation possible (required in further operations)
Corrosion resistant class KBK	2 - moderate corrosion stress
ambient temperature [°C]	-20 to 80
Max. torque of anti-rotation safety [Nm]	0,2
Theoretical force at 6 bar, Return flow [N]	123
Theoretical force at 6 bar, flow [N]	153
Moving mass at 0 mm stroke [g]	24
Weight supplement per 10 mm stroke [g]	13
Base weight at 0 mm stroke [g]	107
Supplement moved mass per 10 mm stroke [g]	4
Fastening type	With female thread With Accessories Selectively:
Pneumatic connection	M5
Cover material	Aluminium wrought alloy
Seals material	NBR TPE-U(PU)
Housing material	aluminium Smooth anodised
Piston rod material	High-alloyed stainless steels