

Intermediate Position SLG-Z-8/12-A - Festo 525680

Item no. FES-525680

Manufacturer Festo

EAN 4052568161903

Festo pneumatic component for industrial automation and compressed-air applications in proven quality.

TECHNICAL DATA

Betriebsdruck max [bar]	8.000000
HS-Code	84123900
Pneumatischer Anschluss	M3
Weight	0.043 kg
Werkstoff	Aluminium



STANDARDS & COMPLIANCE

ISO 8573-1:2010

DESCRIPTION

Festo pneumatic component for industrial automation and compressed-air applications in proven quality. The key technical data of this genuine Festo article are listed below.

installation position	arbitrary
Construction set up	Stopper as rotary drive system,
Position detection	For proximity switch
Operating pressure [bar]	1 to 8
Operating medium	Compressed air to ISO 8573-1:2010 [7:-:-]
Information about operating and control medium	Oiled operation possible (required in further operations)
Corrosion resistant class KBK	2 - moderate corrosion stress
ambient temperature [°C]	-10 to 60
Product weight [g]	33,5
Fastening type	With Throughway bore and dowel pin
Pneumatic connection	M3

esd.equipment

Keldersstr. 15

42697 Solingen, Deutschland

VAT ID: DE269659389

Phone: +49 212 38340680

shop@esd-equipment.com

esd.equipment

Page 1/2

Material information	Copper and PTFE-free
Stoppers material	Nickel-plated steel
Seals material	PUR
Housing material	aluminium Hard anodised