

Vacuum Filter ESF-4B - Festo 191204

Item no. FES-191204

Manufacturer Festo

EAN 4052568150525

Festo vacuum component for safe gripping, holding and handling in automation.

TECHNICAL DATA

Betriebsdruck max [bar]	4.000000
Corrosion resistance class CRC	1 - low corrosion stress
Dichtmaterial	NBR
Filterfeinheit [µm]	10
HS-Code	84213925
Material	Aluminium
Medium	Air
Mounting position	arbitrary
Operating conditions	ISO 8573-1
Pneumatic connection	M6
Temperature (max.)	60
Weight	0.06 kg



STANDARDS & COMPLIANCE

ISO 8573-1:2010

DESCRIPTION

Festo vacuum component for safe gripping, holding and handling in automation. The key technical data of this genuine Festo article are listed below.

installation position	arbitrary
Filter porosity [µm]	10
Operating pressure [bar]	-0.95 to 4
Flow for an under-pressure = -0.75 bar [l/min]	270
Operating medium	Atmospheric air based on ISO 8573-1:2010 [7:-:-]
Corrosion resistant class KBK	1 - low corrosion stress
ambient temperature [°C]	0 to 60
Product weight [g]	19
Fastening type	With Male thread Via vacuum connection
Pneumatic connection	M6
vacuum connection	M6

esd.equipment

Keldersstr. 15

42697 Solingen, Deutschland

VAT ID: DE269659389

Phone: +49 212 38340680

shop@esd-equipment.com

esd.equipment

Page 1/2

Material information	Copper and PTFE-free RoHs compliant
Seals material	NBR
Filter material	PVF
Housing material	aluminium brass nickel-plated