

Suction Cup ESS-50-EN - Festo 189350

Item no. FES-189350

Manufacturer Festo

EAN 4052568042417

Festo vacuum component for safe gripping, holding and handling in automation.

TECHNICAL DATA

Betriebsdruck max [bar]	0.950000
Corrosion resistance class CRC	1 - low corrosion stress
HS-Code	84799070
Medium	Air
Mounting position	arbitrary
Nennweite DN [mm]	3
Series	ESS
Temperature (max.)	70
Weight	0.023 kg



STANDARDS & COMPLIANCE

ISO 8573-1:2010

DESCRIPTION

Festo vacuum component for safe gripping, holding and handling in automation. The key technical data of this genuine Festo article are listed below.

Min. workpiece radius R [mm]	100
Nominal width [mm]	3,0
Suction diameter [mm]	50
Suction volumes [cm ³]	7,900
Connection position	top
installation position	arbitrary
Allocate suction cup fixation	Size 4
Suction shape	Round, extra-deep
Operating pressure [bar]	0 to 0.95
Nominal operating pressure [bar]	-0,7
Operating medium	Atmospheric air based on ISO 8573-1:2010 [7:-:-]

esd.equipment

Keldersstr. 15
42697 Solingen, Deutschland
VAT ID: DE269659389

Phone: +49 212 38340680
shop@esd-equipment.com

esd.equipment

Page 1/2

Corrosion resistant class KBK	1 - low corrosion stress
Food compatibility	See expanded material information
ambient temperature [°C]	-10 to 70
Holding force for nominal operating pressure [N]	103,60
Shear force for nominal operating pressure [N]	115,0
Product weight [g]	23,4
Fastening type	Via vacuum connection
vacuum connection	M6
colour	 black
Shore hardness	60 ± 5
Stud material	brass nickel-plated Alu wrought alloy nickel-plated Zing and chrome plating
Material information	Copper and PTFE-free RoHs compliant
Suction cups material	NBR