

Plug SEA-GS-9 - Festo 18778

Item no. FES-18778

Manufacturer Festo

EAN 4052568022365

Festo pneumatic component for industrial automation and compressed-air applications in proven quality.

TECHNICAL DATA

HS-Code	85366990
Schutzart	IP67
Weight	0.019 kg
Werkstoff	PBT



STANDARDS & COMPLIANCE

EN 61984 EN 175301-803

DESCRIPTION

Festo pneumatic component for industrial automation and compressed-air applications in proven quality. The key technical data of this genuine Festo article are listed below.

Based on standard	EN 61076-2-101 EN 61984
Fastening type	With Threaded sleeve
installation position	arbitrary
Product weight [g]	18,0
Electrical connection	M12x1 4-pin Wiring diagram Form A acc. to EN 175301-803 Straight plug / screw clamp
Operating voltage range DC [V]	$\leq 250\text{ V}$
Operating voltage range AC [V]	$\leq 250\text{ V}$
Current carrying capacity at 40°C [A]	4
Surge voltage strength [kV]	2,5
Cable screwing	Pg9
Permitted cable diameter [mm]	6 to 8

esd.equipment

Keldersstr. 15
42697 Solingen, Deutschland
VAT ID: DE269659389

Phone: +49 212 38340680
shop@esd-equipment.com

esd.equipment

Page 1/2

Connection cross-section [mm²]	0,75
Protection category	IP67
ambient temperature [°C]	-40 to 85
CE certificate (see declaration of conformity)	to EU low voltage directive
Material information	RoHs compliant
Degree of contamination	3
Corrosion resistant class KBK	2 - moderate corrosion stress
Housing material	PBT
Housing colour	 black
Locking nut material	PBT
Plug contacts material	brass White bronze coated