

Sub-Base VMPA1-IC-AP-1 - Festo 533394

Item no. FES-533394

Manufacturer Festo

EAN 4052568086480

Festo fitting or line component for fast, leak-tight and pressure-resistant compressed-air connections.

TECHNICAL DATA

Betriebsdruck max [bar]	8.000000
HS-Code	84819000
Pneumatischer Anschluss	M7
Weight	0.13 kg



DESCRIPTION

Festo fitting or line component for fast, leak-tight and pressure-resistant compressed-air connections. The key technical data of this genuine Festo article are listed below.

Product weight [g]	92,0
Material information	RoHs compliant
Width [mm]	20,2
Length [mm]	107,3
Pitch dimension [mm]	10,5
Operating pressure [bar]	3 to 8
Control pressure [bar]	3 to 8
Corrosion resistant class KBK	0 - No corrosion stressing
ambient temperature [°C]	-5 to 50
Pneumatic connection 2	M7
Pneumatic connection 4	M7
Connection plate material	Aluminium die casting
Pneumatic connection 1	M7
Permission	c UL us - Recognized (OL)

KC-mark	KC-EMV
CE certificate (see declaration of conformity)	to EU EMC directive
Electrical connection	M8 Plug
Fastening type connection plate	With throughway bores
Pneumatic connection 3	M7
Pneumatic connection 5	M7