

One-Way Flow Control Va GR-3/4 - Festo 2103

Item no. FES-2103

Manufacturer Festo

EAN 4052568000080

Festo valve for fast, reliable control of compressed-air direction and flow.

TECHNICAL DATA

Betriebsdruck max [bar]	15.000000
HS-Code	84812090
Pneumatischer Anschluss	G3/4
Weight	0.9 kg
Werkstoff	Aluminium



STANDARDS & COMPLIANCE

ISO 8573-1:2010

DESCRIPTION

Festo valve for fast, reliable control of compressed-air direction and flow. The key technical data of this genuine Festo article are listed below.

Valve function	Throttle blowback function
Pneumatic connection 1	G3/4
Pneumatic connection 2	G3/4
Setting element	knurled screw
Fastening type	Front panel integration With throughway bores
Normal nominal flow in one-way flow control [l/min]	3.300,0
Normal nominal flow in check valve direction [l/min]	4800
Operating pressure [bar]	0.3 to 15
ambient temperature [°C]	-10 to 60

esd.equipment

Keldersstr. 15
42697 Solingen, Deutschland
VAT ID: DE269659389

Phone: +49 212 38340680
shop@esd-equipment.com

esd.equipment

Page 1/2

Housing material	Aluminium wrought alloy
installation position	arbitrary
Operating medium	Compressed air to ISO 8573-1:2010 [7:-:-]
Information about operating and control medium	Oiled operation possible (required in further operations)
Medium temperature [°C]	-10 to 60
Product weight [g]	938,0
Material information	RoHs compliant