

## One-Way Flow Control Va GR-3/8-B - Festo 6308

Item no. FES-6308

Manufacturer Festo

EAN 4052568001209

Festo valve for fast, reliable control of compressed-air direction and flow.

### TECHNICAL DATA

|                         |                |
|-------------------------|----------------|
| Betriebsdruck max [bar] | 10.000000      |
| HS-Code                 | 84812090       |
| Pneumatischer Anschluss | G3/8           |
| Weight                  | 0.25 kg        |
| Werkstoff               | Zink-Druckguss |



### STANDARDS & COMPLIANCE

ISO 8573-1:2010

### DESCRIPTION

Festo valve for fast, reliable control of compressed-air direction and flow. The key technical data of this genuine Festo article are listed below.

|                                                      |                                                                  |
|------------------------------------------------------|------------------------------------------------------------------|
| Valve function                                       | Throttle blowback function                                       |
| Pneumatic connection 1                               | G3/8                                                             |
| Pneumatic connection 2                               | G3/8                                                             |
| Setting element                                      | knurled screw                                                    |
| Fastening type                                       | Front panel integration<br>With throughway bores<br>Selectively: |
| Normal nominal flow in one-way flow control [l/min]  | 1.010,0                                                          |
| Normal nominal flow in check valve direction [l/min] | 1150                                                             |
| Operating pressure [bar]                             | 0.1 to 10                                                        |
| ambient temperature [°C]                             | -20 to 75                                                        |

|                                                |                                                           |
|------------------------------------------------|-----------------------------------------------------------|
| Housing material                               | Zinc pressure cast                                        |
| installation position                          | arbitrary                                                 |
| Operating medium                               | Compressed air to ISO 8573-1:2010 [7:4:4]                 |
| Information about operating and control medium | Oiled operation possible (required in further operations) |
| Medium temperature [°C]                        | -20 to 75                                                 |
| Product weight [g]                             | 225,0                                                     |
| Material information                           | RoHs compliant                                            |
| Regulation screw material                      | Brass                                                     |