

One-Way Flow Control GR-QS-3 - Festo 193965

Item no. FES-193965

Manufacturer Festo

EAN 4052568044145

Festo valve for fast, reliable control of compressed-air direction and flow.

TECHNICAL DATA

Betriebsdruck max [bar]	10.000000
Dichtmaterial	NBR
Funktion	Throttle check valve function
HS-Code	84812090
Material	Polyamide (PA)
Medium	Compressed air
Mounting position	arbitrary
Operating conditions	ISO 8573-1
Pneumatic connection	QS-3
Series	GR
Temperature (max.)	60
Weight	0.013 kg



STANDARDS & COMPLIANCE

ISO 8573-1:2010

DESCRIPTION

Festo valve for fast, reliable control of compressed-air direction and flow. The key technical data of this genuine Festo article are listed below.

Valve function	Throttle blowback function
Pneumatic connection 1	QS-3
Pneumatic connection 2	QS-3
Setting element	knurled screw
Fastening type	Front panel integration With throughway bores With Accessories Selectively:
Normal nominal flow in one-way flow control [l/min]	85,0
Normal nominal flow in check valve direction [l/min]	120
Operating pressure [bar]	0.2 to 10
ambient temperature [°C]	-10 to 60
Housing material	PA reinforced

esd.equipment

Keldersstr. 15

42697 Solingen, Deutschland

VAT ID: DE269659389

Phone: +49 212 38340680

shop@esd-equipment.com

esd.equipment

Page 1/2

installation position	arbitrary
Operating medium	Compressed air to ISO 8573-1:2010 [7:4:4]
Information about operating and control medium	Oiled operation possible (required in further operations)
Medium temperature [°C]	-10 to 60
Product weight [g]	12,0
Material information	RoHs compliant
Seals material	NBR
Regulation screw material	High-alloyed steel
Sleeve material	POM