

One-Way Flow Control GRLA-1/8-QS-3-D - Festo 193142

Item no. FES-193142

Manufacturer Festo

EAN 4052568043827


Festo valve for fast, reliable control of compressed-air direction and flow.

TECHNICAL DATA

HS-Code 84812090

Pneumatischer Anschluss QS-3

Weight 0.02 kg



STANDARDS & COMPLIANCE

ISO 8573-1:2010

DESCRIPTION

Festo valve for fast, reliable control of compressed-air direction and flow. The key technical data of this genuine Festo article are listed below.

Valve function	Exhaust air flow control return function
Pneumatic connection 1	QS-3
Pneumatic connection 2	G1/8
Setting element	slotted screw
Fastening type	Screwable
Normal nominal flow in one-way flow control [l/min]	130
Normal nominal flow in check valve direction [l/min]	100 to 130
ambient temperature [°C]	-10 to 60
Maritime classification	see Certificate
installation position	arbitrary
Normal flow In one-way flow control 6 -> 0 bar [l/min]	180

esd.equipment

Keldersstr. 15
42697 Solingen, Deutschland
VAT ID: DE269659389

Phone: +49 212 38340680
shop@esd-equipment.com

esd.equipment

Page 1/2

Normal flow In check valve direction 6 -> 0 bar [l/min]	200 to 220
Operating medium	Compressed air to ISO 8573-1:2010 [7:4:4]
Information about operating and control medium	Oiled operation possible (required in further operations)
Medium temperature [°C]	-10 to 60
Product weight [g]	22,0
Stud material	Aluminium wrought alloy
Material information	RoHs compliant
Seals material	NBR
Regulation screw material	Brass
Swivel connection material	Chromatised Zinc pressure cast
Operating pressure complete temperature range [bar]	0.2 to 10
Nominal tightening torque [Nm]	3,0
Tolerance to nominal tightening torque	± 10 %
Sleeve material	POM