

One-Way Flow Control GRLA-M5-QS-3-D - Festo 193137

Item no.	FES-193137	Manufacturer	Festo
Manufacturer no.	GRLA-M5-QS-3-D	EAN	4052568043797

Festo valve for fast, reliable control of compressed-air direction and flow.

TECHNICAL DATA

Article authenticity	Original product
Condition of article	New
HS-Code	84812090
Pneumatischer Anschluss	QS-3
Weight	0.013 kg



STANDARDS & COMPLIANCE

ISO 8573-1:2010

DESCRIPTION

Festo valve for fast, reliable control of compressed-air direction and flow. The key technical data of this genuine Festo article are listed below.

Valve function	Exhaust air flow control return function
Pneumatic connection 1	QS-3
Pneumatic connection 2	M5
Setting element	slotted screw
Fastening type	Screwable
Normal nominal flow in one-way flow control [l/min]	100
Normal nominal flow in check valve direction [l/min]	60 to 100
ambient temperature [°C]	-10 to 60
Maritime classification	see Certificate
installation position	arbitrary
Normal flow In one-way flow control 6 -> 0 bar [l/min]	145
Normal flow In check valve direction 6 -> 0 bar [l/min]	150 to 170
Operating medium	Compressed air to ISO 8573-1:2010 [7:4:4]

Information about operating and control medium	Oiled operation possible (required in further operations)
Medium temperature [°C]	-10 to 60
Product weight [g]	13,0
Stud material	Brass
Material information	RoHs compliant
Seals material	NBR
Regulation screw material	Brass
Swivel connection material	Chromatised Zinc pressure cast
Operating pressure complete temperature range [bar]	0.2 to 10
Nominal tightening torque [Nm]	0,8
Tolerance to nominal tightening torque	± 10 %
Sleeve material	POM