

Flow Control Valve GRLO-M5-QS-3-LF-C - Festo 175054

Item no. FES-175054

Manufacturer Festo

EAN 4052568037727

Festo valve for fast, reliable control of compressed-air direction and flow.

TECHNICAL DATA

Betriebsdruck max [bar] **10.000000**

HS-Code **84812090**

Pneumatischer Anschluss **M5**

Weight **0.012 kg**



STANDARDS & COMPLIANCE

ISO 8573-1:2010

DESCRIPTION

Festo valve for fast, reliable control of compressed-air direction and flow. The key technical data of this genuine Festo article are listed below.

Valve function	Throttle function
Pneumatic connection 1	M5
Pneumatic connection 2	QS-3
Setting element	slotted screw
Fastening type	Screwable
Normal nominal flow in one-way flow control [l/min]	40
Operating pressure [bar]	0 to 10
ambient temperature [°C]	-10 to 60
installation position	arbitrary
Normal flow In one-way flow control 6 -> 0 bar [l/min]	80
Operating medium	Compressed air to ISO 8573-1:2010 [7:4:4]

Information about operating and control medium	Oiled operation possible (required in further operations)
Medium temperature [°C]	-10 to 60
Max. tightening torque [Nm]	1,5
Product weight [g]	9
Stud material	Brass
Material information	RoHs compliant
Seals material	NBR
Regulation screw material	Brass
Swivel connection material	Zinc pressure cast
Sleeve material	POM