

Pneumatic Valve CJ-5/2-1/4 - Festo 5736

Item no. FES-5736

Manufacturer Festo

EAN 4052568110710

Festo valve for fast, reliable control of compressed-air direction and flow.

TECHNICAL DATA

Betriebsdruck max [bar]	16.000000
HS-Code	84812090
Pneumatischer Anschluss	G1/4
Weight	0.29 kg
Werkstoff	Aluminium



STANDARDS & COMPLIANCE

ISO 8573-1:2010

DESCRIPTION

Festo valve for fast, reliable control of compressed-air direction and flow. The key technical data of this genuine Festo article are listed below.

Valve function	5/2 bistable
Actuation type	pneumatic
Normal nominal flow [l/min]	1.400
Operating pressure [bar]	1 to 16
Nominal width [mm]	6,5
installation position	arbitrary
Hand assist actuation	tentative
Control pressure [bar]	2 to 10
Max. switching frequency [Hz]	40
Shifting time on [ms]	28
Operating medium	Compressed air to ISO 8573-1:2010 [7:4:4]

esd.equipment

Keldersstr. 15
42697 Solingen, Deutschland
VAT ID: DE269659389

Phone: +49 212 38340680
shop@esd-equipment.com

esd.equipment

Page 1/2

Information about operating and control medium	Oiled operation possible (required in further operations)
Medium temperature [°C]	-10 to 60
Fastening type	on connection plate
Control air 12 connection	G1/8
Control air 14 connection	G1/8
Pneumatic connection 1	G1/4
Pneumatic connection 2	G1/4
Pneumatic connection 3	G1/4
Pneumatic connection 4	G1/4
Pneumatic connection 5	G1/4
Material information	LABS containing materials included
Seals material	NBR
Housing material	Aluminium wrought alloy
Diaphragm material	PUR