

Foot Valve F-5-1/4-B - Festo 8992

Item no. FES-8992

Manufacturer Festo

EAN 4052568008833

Festo valve for fast, reliable control of compressed-air direction and flow.

TECHNICAL DATA

Actuation type	Manually
Betriebsdruck max [bar]	10.000000
Design	Plate seat
Dichtmaterial	NBR
Durchfluss [l/min]	550
Funktion	5/2 monostabil
HS-Code	84812090
Medium	Druckluft
Mounting position	arbitrary
Nennweite DN [mm]	7
Pneumatischer Anschluss	G1/4
Temperature (max.)	60
Weight	0.7 kg
Werkstoff	Aluminium



STANDARDS & COMPLIANCE

ISO 8573-1:2010

DESCRIPTION

Festo valve for fast, reliable control of compressed-air direction and flow. The key technical data of this genuine Festo article are listed below.

Valve function	5/2 monostable
Actuation type	Manually
Normal nominal flow [l/min]	550
Operating pressure [bar]	-0.95 to 10
Construction set up	Plate seat
Reset mode	Mechanical spring
Nominal width [mm]	7
installation position	arbitrary
Control type	Direct
Flow direction	Not reversible

esd.equipment

Keldersstr. 15

42697 Solingen, Deutschland

VAT ID: DE269659389

Phone: +49 212 38340680

shop@esd-equipment.com

esd.equipment

Page 1/2

Operating medium	Compressed air to ISO 8573-1:2010 [7:4:4]
ambient temperature [°C]	-10 to 60
actuating force [N]	78,0
Product weight [g]	705
Fastening type	With throughway bores
Pneumatic connection 1	G1/4
Pneumatic connection 2	G1/4
Pneumatic connection 3	G1/4
Seals material	NBR
Housing material	Aluminium die casting
Pneumatic connection 4	G1/4
Pneumatic connection 5	G1/4