

Flanged Pressure Gaug FMA-50-16-1/4-EN - Festo 159600

Item no. FES-159600

Manufacturer Festo

EAN 4052568071660

Festo pneumatic component for industrial automation and compressed-air applications in proven quality.

TECHNICAL DATA

Betriebsdruck max [bar]	16.000000
HS-Code	90262040
Pneumatischer Anschluss	G1/4
Schutzart	IP43
Weight	0.11 kg



DESCRIPTION

Festo pneumatic component for industrial automation and compressed-air applications in proven quality. The key technical data of this genuine Festo article are listed below.

Display range [bar] [bar]	0 to 16
Complies to standard	EN 837-1
Nominal size pressure gauge	50
Construction set up	Pipe spring pressure gauge
Fastening type	Front panel integration
Operating medium	Inert gases Neutral liquids
Operating pressure [bar]	0 to 16
Factor alternating strain	0.66
Measurement precision class	2,5
Protection category	IP43
Medium temperature [°C]	-20 to 60
ambient temperature [°C]	-20 to 60
Material information	RoHs compliant
Connection position	Back side centred

Pneumatic connection	G1/4
From medium contacting materials	Brass
Stud material	Brass
Housing material	ABS
Window material	SAN
Fastening ring material	Steel
Housing colour	> black
Product weight [g]	100
Information about operating and control medium	No acetylene No oxygen