

Foot Valve With Deten FPB-3-1/4 - Festo 526984

Item no. FES-526984

Manufacturer Festo

EAN 4052568162528

Festo valve for fast, reliable control of compressed-air direction and flow.

TECHNICAL DATA

Betriebsdruck max [bar]	10.000000
HS-Code	84812090
Pneumatischer Anschluss	G1/4
Weight	0.65 kg
Werkstoff	Aluminium



STANDARDS & COMPLIANCE

ISO 8573-1:2010

DESCRIPTION

Festo valve for fast, reliable control of compressed-air direction and flow. The key technical data of this genuine Festo article are listed below.

Valve function	3/2 bistable
Actuation type	Manually
Normal nominal flow [l/min]	550
Operating pressure [bar]	-0.95 to 10
Construction set up	Plate seat
Reset mode	Mechanical spring
Nominal width [mm]	7
installation position	arbitrary
Control type	Direct
Flow direction	Not reversible
Operating medium	Compressed air to ISO 8573-1:2010 [7:4:4]

esd.equipment

Keldersstr. 15
42697 Solingen, Deutschland
VAT ID: DE269659389

Phone: +49 212 38340680
shop@esd-equipment.com

esd.equipment

Page 1/2

ambient temperature [°C]	-10 to 60
actuating force [N]	31,5
Product weight [g]	610
Fastening type	With throughway bores
Pneumatic connection 1	G1/4
Pneumatic connection 2	G1/4
Pneumatic connection 3	G1/4
Seals material	NBR
Housing material	Aluminium die casting