

One-Way Flow Control Va GG-1/4-3/8 - Festo 3633

Item no. FES-3633

Manufacturer Festo

EAN 4052568110352

Festo valve for fast, reliable control of compressed-air direction and flow.

TECHNICAL DATA

Betriebsdruck max [bar]	8.000000
HS-Code	84812090
Pneumatischer Anschluss	G1/4
Weight	0.37 kg
Werkstoff	Aluminium



STANDARDS & COMPLIANCE

ISO 8573-1:2010

DESCRIPTION

Festo valve for fast, reliable control of compressed-air direction and flow. The key technical data of this genuine Festo article are listed below.

Valve function	Throttle blowback function
Pneumatic connection 1	G1/4
Pneumatic connection 2	G1/4
Setting element	Roller lever
Fastening type	With throughway bores
Normal nominal flow in one-way flow control [l/min]	870
Normal nominal flow in check valve direction [l/min]	1.150
Operating pressure [bar]	0.03 to 8
ambient temperature [°C]	-10 to 60
Housing material	Aluminium wrought alloy
installation position	arbitrary

esd.equipment

Keldersstr. 15
42697 Solingen, Deutschland
VAT ID: DE269659389

Phone: +49 212 38340680
shop@esd-equipment.com

esd.equipment

Page 1/2

Operating medium	Compressed air to ISO 8573-1:2010 [7:-:-]
Information about operating and control medium	Oiled operation possible (required in further operations)
Medium temperature [°C]	-10 to 60
Product weight [g]	380
Actuation type	Mechanical
Operating pressure [psi] [psi]	0,43 bis 116
Seals material	NBR