

Exhaust Air Flow Contr GRE-3/8 - Festo 35310

Item no. FES-35310

Manufacturer Festo

EAN 4052568010119

Festo valve for fast, reliable control of compressed-air direction and flow.

TECHNICAL DATA

Betriebsdruck max [bar] 10.000000

HS-Code 84812090

Pneumatischer Anschluss G3/8

Weight 0.06 kg



STANDARDS & COMPLIANCE

ISO 8573-1:2010

DESCRIPTION

Festo valve for fast, reliable control of compressed-air direction and flow. The key technical data of this genuine Festo article are listed below.

Valve function	Throttle silencer function
Pneumatic connection 1	G3/8
Setting element	slotted screw
Fastening type	Screwable
Normal nominal flow in one-way flow control [l/min]	2.000
Normal flow 6 -> 0 bar [l/min]	3 to 2000
ambient temperature [°C]	-10 to 70
installation position	arbitrary
Operating medium	Compressed air to ISO 8573-1:2010 [7:4:4]
Information about operating and control medium	Oiled operation possible (required in further operations)
Medium temperature [°C]	-10 to 70

esd.equipment

Keldersstr. 15

42697 Solingen, Deutschland

VAT ID: DE269659389

Phone: +49 212 38340680

shop@esd-equipment.com

esd.equipment

Page 1/2

Product weight [g]	50
Stud material	Aluminium wrought alloy
Material information	RoHs compliant
Seals material	NBR
Regulation screw material	Brass
Operating pressure [bar]	0 to 10
Max. tightening torque [Nm]	15