

Non-Return Valve HA-3/8-QS-12 - Festo 153458

Item no. FES-153458

Manufacturer Festo

EAN 4052568070670

Festo valve for fast, reliable control of compressed-air direction and flow.

TECHNICAL DATA

Betriebsdruck max [bar] **10.000000**

HS-Code **84813099**

Pneumatischer Anschluss **R3/8**

Weight **0.05 kg**

Werkstoff **Aluminium**



STANDARDS & COMPLIANCE

ISO 8573-1:2010

DESCRIPTION

Festo valve for fast, reliable control of compressed-air direction and flow. The key technical data of this genuine Festo article are listed below.

Valve function	Check valve function
Pneumatic connection 1	R3/8
Pneumatic connection 2	QS-12
Fastening type	Screwable
Operating pressure [bar]	-1 to 10
ambient temperature [°C]	0 to 60
Housing material	Anodized aluminium
Operating medium	Compressed air to ISO 8573-1:2010 [7:-:-]
Information about operating and control medium	Oiled operation possible (required in further operations)
Product weight [g]	50,0
Material information	RoHs compliant

esd.equipment

Keldersstr. 15

42697 Solingen, Deutschland

VAT ID: DE269659389

Phone: +49 212 38340680

shop@esd-equipment.com

esd.equipment

Page 1/2

Normal nominal flow [l/min]	1.876
Min. open differential pressure [bar]	0,1
Min. close differential pressure [bar]	0,2
Housing colour	 silver