

Manual Override HAB-1/4 - Festo 184586

Item no. FES-184586

Manufacturer Festo

EAN 4052568014490

Festo pneumatic component for industrial automation and compressed-air applications in proven quality.

TECHNICAL DATA

Betriebsdruck max [bar]	10.000000
HS-Code	84812090
Pneumatischer Anschluss	G1/4
Weight	0.016 kg
Werkstoff	Aluminium



STANDARDS & COMPLIANCE

ISO 8573-1:2010

DESCRIPTION

Festo pneumatic component for industrial automation and compressed-air applications in proven quality. The key technical data of this genuine Festo article are listed below.

installation position	arbitrary
Corrosion resistant class KBK	2 - moderate corrosion stress
ambient temperature [°C]	-20 to 80
Fastening type	Screwable
Housing material	Aluminium wrought alloy anodized
Material information	RoHs compliant
Nominal width [mm]	7,0
Valve function	Venting element
Operating pressure [bar]	0 to 10
Normal nominal flow venting [l/min]	165
Operating medium	Compressed air to ISO 8573-1:2010 [7:4:4]

Information about operating and control medium	Oiled operation possible (required in further operations)
Medium temperature [°C]	-20 to 80
Pneumatic connection 1	G1/4
Pneumatic connection 2	G1/4