

# Non-Return Valve HB-3/8-QS-10 - Festo 153457

Item no. FES-153457

Manufacturer Festo

EAN 4052568070663

Festo valve for fast, reliable control of compressed-air direction and flow.

## TECHNICAL DATA

|                         |                    |
|-------------------------|--------------------|
| Betriebsdruck max [bar] | 10.000000          |
| Durchfluss [l/min]      | 1700               |
| Funktion                | Rückschlagfunktion |
| HS-Code                 | 84813099           |
| Medium                  | Druckluft          |
| Pneumatischer Anschluss | QS-10              |
| Serie                   | HB                 |
| Temperature (max.)      | 60                 |
| Weight                  | 0.048 kg           |
| Werkstoff               | Aluminium          |



## STANDARDS & COMPLIANCE

ISO 8573-1:2010

## DESCRIPTION

Festo valve for fast, reliable control of compressed-air direction and flow. The key technical data of this genuine Festo article are listed below.

|                                                |                                                           |
|------------------------------------------------|-----------------------------------------------------------|
| Valve function                                 | Check valve function                                      |
| Pneumatic connection 1                         | QS-10                                                     |
| Pneumatic connection 2                         | R3/8                                                      |
| Fastening type                                 | Screwable                                                 |
| Operating pressure [bar]                       | -1 to 10                                                  |
| ambient temperature [°C]                       | 0 to 60                                                   |
| Housing material                               | Anodized aluminium                                        |
| Operating medium                               | Compressed air to ISO 8573-1:2010 [7:-:-]                 |
| Information about operating and control medium | Oiled operation possible (required in further operations) |
| Product weight [g]                             | 47,0                                                      |
| Material information                           | RoHs compliant                                            |

**esd.equipment**

Keldersstr. 15  
42697 Solingen, Deutschland  
VAT ID: DE269659389

Phone: +49 212 38340680  
shop@esd-equipment.com

**esd.equipment**

Page 1/2

|                                        |                                                                     |
|----------------------------------------|---------------------------------------------------------------------|
| Normal nominal flow [l/min]            | 1.700                                                               |
| Min. open differential pressure [bar]  | 0,1                                                                 |
| Min. close differential pressure [bar] | 0,2                                                                 |
| Housing colour                         | <span class="farbe" style="background-color:#EDEDED"></span> silver |