

Shut-Off Valve HE-2-QS-8 - Festo 153468

Item no.	FES-153468	Manufacturer	Festo
Manufacturer no.	HE-2-QS-8	EAN	4052568034856

Festo valve for fast, reliable control of compressed-air direction and flow.

TECHNICAL DATA

Article authenticity	Original product
Betriebsdruck max [bar]	10.000000
Condition of article	New
HS-Code	84812090
Pneumatischer Anschluss	QS-8
Weight	0.026 kg
Werkstoff	PBT



STANDARDS & COMPLIANCE

ISO 8573-1:2010

DESCRIPTION

Festo valve for fast, reliable control of compressed-air direction and flow. The key technical data of this genuine Festo article are listed below.

Valve function	2/2 Bistable
Pneumatic connection 1	QS-8
Pneumatic connection 2	QS-8
Actuation type	Manually
Fastening type	Leitungseinbau wahlweise: Direktbefestigung über Durchgangsbohrung
Normal nominal flow [l/min]	415,8
Nominal width [mm]	3,2
Betriebsdruck Mpa [MPa]	-0,095 bis 1
Operating pressure [bar]	-0.95 to 10
ambient temperature [°C]	0 to 60
Housing material	PBT reinforced

Operating medium	Compressed air to ISO 8573-1:2010 [7:-:-]
Sealing principle	Soft
installation position	arbitrary
Construction set up	Piston pusher
Control type	Direct
Flow direction	Not reversible
Information about operating and control medium	Oiled operation possible (required in further operations)
Corrosion resistant class KBK	2 - moderate corrosion stress
Medium temperature [°C]	0 to 60
Product weight [g]	26
Material information	RoHs compliant
Seals material	NBR