

Shut-Off Valve HE-3-3/8-3/8 - Festo 153298

Item no. FES-153298

Manufacturer Festo

EAN 4052568033668

Festo valve for fast, reliable control of compressed-air direction and flow.

TECHNICAL DATA

Actuation type	Manually
Betriebsdruck max [bar]	10.000000
Corrosion resistance class CRC	2 - moderate corrosion stress
Design	Piston pusher
Dichtmaterial	NBR
Durchfluss [l/min]	797,4
Funktion	3/2 bistabil
HS-Code	84812090
Medium	Druckluft
Mounting position	arbitrary
Nennweite DN [mm]	4,6
Pneumatischer Anschluss	R3/8
Serie	HE
Temperature (max.)	60
Weight	0.08 kg
Werkstoff	PBT



STANDARDS & COMPLIANCE

ISO 8573-1:2010

DESCRIPTION

Festo valve for fast, reliable control of compressed-air direction and flow. The key technical data of this genuine Festo article are listed below.

Valve function	3/2 bistable
Pneumatic connection 1	R3/8
Pneumatic connection 2	R3/8
Actuation type	Manually
Fastening type	wahlweise: Direktbefestigung über Durchgangsbohrung Direktbefestigung über Gewinde
Normal nominal flow [l/min]	797,4
Nominal width [mm]	4,6
Betriebsdruck Mpa [MPa]	-0,095 bis 1

esd.equipment

Keldersstr. 15

42697 Solingen, Deutschland

VAT ID: DE269659389

Phone: +49 212 38340680

shop@esd-equipment.com

esd.equipment

Page 1/2

Operating pressure [bar]	-0.95 to 10
ambient temperature [°C]	0 to 60
Housing material	PBT reinforced
Operating medium	Compressed air to ISO 8573-1:2010 [7:-:-]
Exhaust function	Cannot be throttled
Sealing principle	Soft
installation position	arbitrary
Construction set up	Piston pusher
Control type	Direct
Flow direction	Not reversible
Information about operating and control medium	Oiled operation possible (required in further operations)
Corrosion resistant class KBK	2 - moderate corrosion stress
Medium temperature [°C]	0 to 60
Product weight [g]	79
Pneumatic connection 3	Not recorded
Stud material	Nickel-plated brass
Material information	RoHs compliant
Seals material	NBR