

Shut-Off Valve HE-3-QS-12 - Festo 153478

Item no. FES-153478

Manufacturer Festo

EAN 4052568034948

Festo valve for fast, reliable control of compressed-air direction and flow.

TECHNICAL DATA

Betriebsdruck max [bar]	10.000000
HS-Code	84812090
Pneumatischer Anschluss	QS-12
Weight	0.048 kg
Werkstoff	PBT



STANDARDS & COMPLIANCE

ISO 8573-1:2010

DESCRIPTION

Festo valve for fast, reliable control of compressed-air direction and flow. The key technical data of this genuine Festo article are listed below.

Valve function	3/2 bistable
Pneumatic connection 1	QS-12
Pneumatic connection 2	QS-12
Actuation type	Manually
Fastening type	Leitungseinbau wahlweise: Direktbefestigung über Durchgangsbohrung
Normal nominal flow [l/min]	788,4
Nominal width [mm]	3,3
Betriebsdruck Mpa [MPa]	-0,095 bis 1
Operating pressure [bar]	-0.95 to 10
ambient temperature [°C]	0 to 60
Housing material	PBT reinforced

esd.equipment

Keldersstr. 15
42697 Solingen, Deutschland
VAT ID: DE269659389

Phone: +49 212 38340680
shop@esd-equipment.com

esd.equipment

Page 1/2

Operating medium	Compressed air to ISO 8573-1:2010 [7:-:-]
Exhaust function	Cannot be throttled
Sealing principle	Soft
installation position	arbitrary
Construction set up	Piston pusher
Control type	Direct
Flow direction	Not reversible
Information about operating and control medium	Oiled operation possible (required in further operations)
Corrosion resistant class KBK	2 - moderate corrosion stress
Medium temperature [°C]	0 to 60
Product weight [g]	47
Pneumatic connection 3	Not recorded
Material information	RoHs compliant
Seals material	NBR