

Piloted Check Valve HGL-1/4-B - Festo 530031

Item no. FES-530031

Manufacturer Festo

EAN 4052568006839

Festo pneumatic component for industrial automation and compressed-air applications in proven quality.

TECHNICAL DATA

Betriebsdruck max [bar] 10.000000

HS-Code 84813099

Pneumatischer Anschluss G1/4

Weight 0.042 kg



STANDARDS & COMPLIANCE

ISO 8573-1:2010

DESCRIPTION

Festo pneumatic component for industrial automation and compressed-air applications in proven quality. The key technical data of this genuine Festo article are listed below.

Valve function	Unlockable check valve function
Pneumatic connection 1	G1/4
Pneumatic connection 2	G1/4
Actuation type	pneumatic
Control air 21 connection	G1/8
Fastening type	Screwable With Male thread
Operating pressure [bar]	0.5 to 10
Control pressure [bar]	2 to 10
ambient temperature [°C]	-10 to 60
Operating medium	Compressed air to ISO 8573-1:2010 [7:4:4]
Maritime classification	see Certificate

installation position	arbitrary
Normal flow 1 -> 2 from 6 to 0 bar [l/min]	680
Normal nominal flow 1 -> 2 from 6 to 5 bar [l/min]	550
Information about operating and control medium	Oiled operation possible (required in further operations)
Corrosion resistant class KBK	2 - moderate corrosion stress
Bearing temperature [°C]	-10 to 60
Medium temperature [°C]	-10 to 60
control medium	Compressed air to ISO 8573-1:2010 [7:4:4]
Nominal tightening torque [Nm]	11,00
Tolerance to nominal tightening torque	± 10 %
Product weight [g]	41,2
Material information	Copper and PTFE-free RoHs compliant
Seals material	NBR
Banjo bolt material	Aluminium wrought alloy anodized
Sleeve material	POM
Check valve collar material	NBR
Swivel connection material	Zinc pressure cast