

Pneumatic Valve J-5-PK-3 - Festo 4503

Item no. FES-4503


Manufacturer Festo

EAN 4052568000639

Festo valve for fast, reliable control of compressed-air direction and flow.

TECHNICAL DATA

Betriebsdruck max [bar]	8.000000
Design	Plate seat
Dichtmaterial	NBR
Durchfluss [l/min]	105
Funktion	5/2 bistable
HS-Code	84812090
Material	Die-cast zinc
Medium	Compressed air
Nennweite DN [mm]	2,5
Temperature (max.)	60
Weight	0.15 kg



STANDARDS & COMPLIANCE

ISO 8573-1:2010

DESCRIPTION

Festo valve for fast, reliable control of compressed-air direction and flow. The key technical data of this genuine Festo article are listed below.

Valve function	5/2 bistable
Normal nominal flow [l/min]	105
Operating pressure [bar]	1 to 8
Construction set up	Plate seat
Nominal width [mm]	2,5
Shifting time um [ms]	9
Operating medium	Compressed air to ISO 8573-1:2010 [7:-:-]
ambient temperature [°C]	0 to 60
Product weight [g]	130
Fastening type	on connection plate on mounting frames With throughway bores Selectively:
Pneumatic connection 1	PK-3

esd.equipment

Keldersstr. 15

42697 Solingen, Deutschland

VAT ID: DE269659389

Phone: +49 212 38340680

shop@esd-equipment.com

esd.equipment

Page 1/2

Pneumatic connection 4	PK-3
Pneumatic connection 5	PK-3
Material information	RoHs compliant
Connection plate material	brass PPS reinforced
Seals material	NBR
Housing material	plastic Zinc pressure cast
Pneumatic connection 2	PK-3
Pneumatic connection 3	PK-3