

Pushbutton Valve K/O-3-PK-3 - Festo 13793

Item no. FES-13793

Manufacturer Festo

EAN 4052568066130

Festo valve for fast, reliable control of compressed-air direction and flow.

TECHNICAL DATA

Betriebsdruck max [bar]	8.000000
Design	Piston seat
Dichtmaterial	NBR
Durchfluss [l/min]	80
Funktion	3/2 open/closed monostable
HS-Code	84812090
Material	Plastic
Medium	Compressed air
Nennweite DN [mm]	2,5
Operating conditions	ISO 8573-1
Temperature (max.)	60
Weight	0.019 kg



STANDARDS & COMPLIANCE

ISO8573-1:2010

DESCRIPTION

Festo valve for fast, reliable control of compressed-air direction and flow. The key technical data of this genuine Festo article are listed below.

Valve function	3/2 open/closed monostable
Normal nominal flow [l/min]	80
Operating pressure [bar]	0 to 8
Nominal width [mm]	2,5
Control type	Direct
ambient temperature [°C]	-10 to 60
Product weight [g]	20
Fastening type	With throughway bores
Pneumatic connection 1	PK-3
Pneumatic connection 2	PK-3
Housing material	Plastic

Construction set up	Piston seat
Operating medium	Compressed air to ISO8573-1:2010 [-::-:-]
Actuation force at basic setting closed [N]	24,0
Actuation force at basic setting open [N]	17,0
Pneumatic connection 3	PK-3
Seals material	NBR