

Solenoid Valve MFH-5-PK-3-L - Festo 11546

Item no. FES-11546

Manufacturer Festo

EAN 4052568111915

Festo valve for fast, reliable control of compressed-air direction and flow.

TECHNICAL DATA

Betriebsdruck max [bar]	8.000000
Design	Plate seat
Dichtmaterial	NBR
Durchfluss [l/min]	105
Funktion	5/2 monostabil
HS-Code	84812090
Medium	Druckluft
Nennweite DN [mm]	2,5
Serie	MFH
Temperature (max.)	40
Weight	0.22 kg
Werkstoff	Aluminium



STANDARDS & COMPLIANCE

ISO 8573-1:2010

DESCRIPTION

Festo valve for fast, reliable control of compressed-air direction and flow. The key technical data of this genuine Festo article are listed below.

Valve function	5/2 monostable
Normal nominal flow [l/min]	105
Operating pressure [bar]	1.5 to 8
Construction set up	Plate seat
Nominal width [mm]	2,5
Operating medium	Compressed air to ISO 8573-1:2010 [7:-:-]
ambient temperature [°C]	-5 to 40
Product weight [g]	270
Fastening type	on connection plate on mounting frames With throughway bores Selectively:
Pneumatic connection 1	PK-3
Pneumatic connection 4	PK-3

esd.equipment

Keldersstr. 15
42697 Solingen, Deutschland
VAT ID: DE269659389

Phone: +49 212 38340680
shop@esd-equipment.com

esd.equipment

Page 1/2

Pneumatic connection 5	PK-3
Material information	RoHs compliant
Connection plate material	aluminium anodized
Seals material	NBR
Housing material	aluminium anodized
Sealing principle	Soft
Shifting time off [ms]	22
Shifting time on [ms]	14
Medium temperature [°C]	-10 to 60
Pneumatic connection 2	PK-3
Pneumatic connection 3	PK-3