

Solenoid Valve MHE2-M1H-3/2O-QS-4 - Festo 196154

Item no. FES-196154

Manufacturer Festo

EAN 4052568080983

Festo valve for fast, reliable control of compressed-air direction and flow.

TECHNICAL DATA

Actuation type	Electrical
Betriebsdruck max [bar]	8.000000
Corrosion resistance class CRC	2 - moderate corrosion stress
Design	Pressure-relieved poppet valve
Dichtmaterial	HNBR, NBR
Durchfluss [l/min]	100
Funktion	3/2 open monostable
HS-Code	84812090
Material	Die-cast zinc
Medium	Compressed air
Mounting position	arbitrary
Nennweite DN [mm]	2
Operating conditions	EN 60068-2-27, EN 60068-2-6, ISO 8573-1
Protection rating	IP65
Series	MHE2
Temperature (max.)	60
Weight	0.07 kg



STANDARDS & COMPLIANCE

ISO 8573-1:2010 EN 60068-2-6 EN 60068-2-27

DESCRIPTION

Festo valve for fast, reliable control of compressed-air direction and flow. The key technical data of this genuine Festo article are listed below.

Valve function	3/2 open monostable
Actuation type	Electrical
Build.width [mm]	10
Normal nominal flow [l/min]	100
Operating pressure [bar]	-0.9 to 8
Construction set up	Pressure-relieved poppet valve
Reset mode	Mechanical spring

esd.equipment

Keldersstr. 15
42697 Solingen, Deutschland
VAT ID: DE269659389

Phone: +49 212 38340680
shop@esd-equipment.com

esd.equipment

Page 1/3

Protection category	IP65
Permission	c UL us - Recognized (OL)
Nominal width [mm]	2
Pitch dimension [mm]	14
Exhaust function	Can be throttled
Sealing principle	Soft
installation position	arbitrary
Hand assist actuation	tentative
Control type	Direct
Flow direction	Reversible with limitations
Überdeckung	negative Überdeckung
Operating pressure reversible [bar]	-0.9 to 1
Max. switching frequency [Hz]	130
Shifting time off [ms]	3,5
Shifting time on [ms]	7,0
Power-on time	100 %
Coil characteristic value	24 V DC: 2,88 W
Permitted voltage oscillations	± 10 %
Operating medium	Compressed air to ISO 8573-1:2010 [7:4:4]
Information about operating and control medium	Oiled operation possible (required in further operations)
Oscillation strength	Transport use test with severity level 2 to FN 942017-4 and EN 60068-2-6
Shock resistance	Shock test with degree of severity 2 to FN 942017-5 and EN 60068-2-27
Corrosion resistant class KBK	2 - moderate corrosion stress
Medium temperature [°C]	-5 to 60
ambient temperature [°C]	-5 to 60
Product weight [g]	60
Electrical connection	2 pin Plug
Fastening type	With throughway bores
Pneumatic connection 2	QS-4
Material information	Copper and PTFE-free RoHs compliant
Seals material	HNBR NBR
Housing material	Coated Zinc pressure cast
Screws material	Steel zinc plating
Pneumatic connection 11	QS-4

