

Plug SEA-5GS-11-DUO - Festo 192010

Item no. FES-192010

Manufacturer Festo

EAN 4052568043681

Festo pneumatic component for industrial automation and compressed-air applications in proven quality.

TECHNICAL DATA

HS-Code	85366990
Schutzart	IP65
Weight	0.025 kg
Werkstoff	Polyamid (PA)



STANDARDS & COMPLIANCE

EN 61984 EN 175301-803

DESCRIPTION

Festo pneumatic component for industrial automation and compressed-air applications in proven quality. The key technical data of this genuine Festo article are listed below.

Based on standard	EN 61076-2-101 EN 61984
Fastening type	With Threaded sleeve
installation position	arbitrary
Product weight [g]	24,0
Electrical connection	M12x1 5-pin Wiring diagram Form A acc. to EN 175301-803 Straight plug / screw clamp
Operating voltage range DC [V]	$\leq 60\text{ V}$
Operating voltage range AC [V]	$\leq 60\text{ V}$
Current carrying capacity at 40°C [A]	4
Surge voltage strength [kV]	1,5
Cable screwing	Pg11

Permitted cable diameter [mm]	2 x 2.5 - 2,9 mm or 2 x 5 mm
Connection cross-section [mm²]	0.14 to 0.5
Protection category	IP65
ambient temperature [°C]	-40 to 85
CE certificate (see declaration of conformity)	to EU low voltage directive
Material information	RoHs compliant
Degree of contamination	3
Corrosion resistant class KBK	2 - moderate corrosion stress
Housing material	PA
Housing colour	 black
Locking nut material	PA
Plug contacts material	brass White bronze coated