

Proximity Sensor SIEN-M30NB-NS-K-L - Festo 150440

Item no. FES-150440

Manufacturer Festo

EAN 4052568069506

Festo sensor for reliable monitoring of position, pressure or status in the pneumatic system.

TECHNICAL DATA

HS-Code	85365019
Schutzart	IP67
Weight	0.185 kg
Werkstoff	Messing



DESCRIPTION

Festo sensor for reliable monitoring of position, pressure or status in the pneumatic system. The key technical data of this genuine Festo article are listed below.

Complies to standard	EN 60947-5-2
Permission	c UL us - Listed (OL) RCM Mark
CE certificate (see declaration of conformity)	to EU EMC directive
Material information	Copper and PTFE-free RoHs compliant
Measurement switching distance [mm]	15,0
Secured safety distance [mm]	12,15
Reduction factors	aluminium = 0,5 Steel pc. 37 = 1.0 stainless steel St 18/8 = 0,85 Copper = 0.43 brass = 0,53
ambient temperature [°C]	-25 to 70
Repeatability [mm]	0,75
Control output	NPN
Switching element function	NO contact
Max. switching frequency [Hz]	700
Max. output current [mA]	200

Voltage drop [V]	<= 2 V
Short circuit resistance	Cycling
Operating voltage range DC [V]	10 to 30
residual ripple	± 20 %
Empty run current [mA]	<= 10 mA
Reverse polarity protection	for all electrical connections
Electrical connection	3-wire cable
Cable length [MTR]	2,5
Cable sleeve material	TPE-U(PUR)
size	M30x1,5
Fastening type	With locking nut
Integration type	not flush
Product weight [g]	150,0
Housing material	PBTP brass Chrome plated
Switching status indicator	LED yellow
Protection category	IP67
Ambient temperature for moving cable placements [°C]	-5 to 70
Surge voltage strength [kV]	0,8
Degree of contamination	3
Hysteresis [mm]	<= 1,65 mm
Torque [Nm]	40