

Proximity Sensor SIEN-M5B-NO-K-L - Festo 150372

Item no. FES-150372

Manufacturer Festo

EAN 4052568068820

Festo sensor for reliable monitoring of position, pressure or status in the pneumatic system.

TECHNICAL DATA

HS-Code	85365019
Schutzart	IP67
Weight	0.047 kg
Werkstoff	Edelstahl



DESCRIPTION

Festo sensor for reliable monitoring of position, pressure or status in the pneumatic system. The key technical data of this genuine Festo article are listed below.

Complies to standard	EN 60947-5-2
Permission	RCM mark c UL us - Listed (OL)
CE certificate (see declaration of conformity)	to EU EMC directive
Material information	Copper and PTFE-free RoHs compliant
Measurement switching distance [mm]	0,8
ambient temperature [°C]	-25 to 70
Control output	NPN
Switching element function	NC contact
Max. switching frequency [Hz]	5.000
Max. output current [mA]	200
Short circuit resistance	Cycling
Operating voltage range DC [V]	10 to 30
Reverse polarity protection	for all electrical connections
Electrical connection	3-wire cable

Cable length [MTR]	2,5
Cable sleeve material	TPE-U(PUR)
size	M5x0,5
Integration type	flush
Product weight [g]	33,6
Housing material	PA High-alloyed stainless steels
Switching status indicator	LED yellow
Protection category	IP67
Repeatability at constant conditions	0.01 mm
Ambient temperature for moving cable placements [°C]	-5 to 70
Surge voltage strength [kV]	1,0
Corrosion resistant class KBK	4 - particularly severe corrosion stress
Degree of contamination	3