

Proximity Sensor SIES-Q8B-NO-K-L - Festo 174550

Item no. FES-174550


Manufacturer Festo

EAN 4052568074968

Festo sensor for reliable monitoring of position, pressure or status in the pneumatic system.

TECHNICAL DATA

HS-Code	85365019
Schutzart	IP67
Weight	0.05 kg
Werkstoff	Zink-Druckguss



DESCRIPTION

Festo sensor for reliable monitoring of position, pressure or status in the pneumatic system. The key technical data of this genuine Festo article are listed below.

Complies to standard	EN 60947-5-2
Permission	RCM mark c UL us - Listed (OL)
CE certificate (see declaration of conformity)	to EU EMC directive
Material information	Copper and PTFE-free RoHs compliant
Measurement switching distance [mm]	1,5
Secured safety distance [mm]	1,20
Reduction factors	aluminium = 0,45 stainless steel St 18/8 = 0,8 Copper = 0.4 Steel pc. 37 = 1.0 brass = 0,55
ambient temperature [°C]	-25 to 70
Repeatability [mm]	0,07
Control output	NPN
Switching element function	NC contact
Max. switching frequency [Hz]	3.500

Max. switching frequency DC [Hz]	1.500
Voltage drop [V]	2,0
Short circuit resistance	Cycling
Operating voltage range DC [V]	10 to 30
residual ripple	10 %
Empty run current [mA]	<= 10 mA
Reverse polarity protection	for all electrical connections
Electrical connection	3-wire cable
Cable length [MTR]	2,5
Cable sleeve material	TPE-U(PUR)
size	8x8x40 mm
Fastening type	with female thread
Integration type	flush
Product weight [g]	39
Housing material	Chrome plated nickel-plated Zinc pressure cast
Switching status indicator	LED yellow
Protection category	IP67
Max. output current [mA]	200