

Transmitter SOEG-S-M18-S-L - Festo 537703

Item no. FES-537703

Manufacturer Festo

EAN 4052568088743

Festo pneumatic component for industrial automation and compressed-air applications in proven quality.

TECHNICAL DATA

HS-Code	85365019
Schutzart	IP65
Weight	0.07 kg
Werkstoff	Messing



DESCRIPTION

Festo pneumatic component for industrial automation and compressed-air applications in proven quality. The key technical data of this genuine Festo article are listed below.

Design	round
Complies to standard	EN 60947-5-2
Permission	RCM mark c UL us - Listed (OL)
CE certificate (see declaration of conformity)	to EU EMC directive
Material information	Copper and PTFE-free
Measured parameter	Position
Measurement principle	Optoelectronic
Measurement process	one-way light barrier Sender
Light type	 red
Range [mm]	20.000
ambient temperature [°C]	-25 to 55
Short circuit resistance	Cycling
Operating voltage range DC [V]	10 to 36

residual ripple	20 %
Empty run current [mA]	15
Reverse polarity protection	for all electrical connections
Electrical connection	M12x1 3 pin Plug
size	M18x1
Fastening type	With locking nut
Torque [Nm]	20
Product weight [g]	40
Housing material	brass Chrome plated
Locking nut material	brass Chrome plated
Ambient temperature for moving cable placements [°C]	-5 to 55
Protection category	IP65 IP67
Corrosion resistant class KBK	1 - low corrosion stress