

Front Panel Valve SV-3-M5 - Festo 6817

Item no. FES-6817

Manufacturer Festo

EAN 4052568001384

Festo valve for fast, reliable control of compressed-air direction and flow.

TECHNICAL DATA

Betriebsdruck max [bar]	8.000000
HS-Code	84812090
Pneumatischer Anschluss	M5
Weight	0.038 kg
Werkstoff	Messing



STANDARDS & COMPLIANCE

ISO8573-1:2010

DESCRIPTION

Festo valve for fast, reliable control of compressed-air direction and flow. The key technical data of this genuine Festo article are listed below.

Valve function	3/2 closed monostable
Actuation type	Manually
Normal nominal flow [l/min]	65
Operating pressure [bar]	-0.95 to 8
Construction set up	Poppet valve with reset spring
Reset mode	Mechanical spring
Nominal width [mm]	2,0
Sealing principle	Soft
installation position	arbitrary
Control type	Direct
Überdeckung	positive Überdeckung

Operating medium	Compressed air to ISO8573-1:2010 [-:-:-]
ambient temperature [°C]	-10 to 60
actuating force [N]	12,0
Product weight [g]	40
Fastening type	Front panel integration With throughway bores
Pneumatic connection 1	M5
Seals material	NBR
Housing material	plastic brass