

Front Panel Valve SVS-3-1/8 - Festo 10190

Item no. FES-10190

Manufacturer Festo

EAN 4052568009007

Festo valve for fast, reliable control of compressed-air direction and flow.

TECHNICAL DATA

Actuation type	Mechanical
Betriebsdruck max [bar]	8.000000
Design	Piston seat
Dichtmaterial	NBR, TPE-U(PU)
Durchfluss [l/min]	120
Funktion	3/2 closed monostable
HS-Code	84812090
Material	Aluminium
Medium	Compressed air
Mounting position	arbitrary
Pneumatic connection	G1/8
Temperature (max.)	60
Weight	0.095 kg



STANDARDS & COMPLIANCE

ISO8573-1:2010

DESCRIPTION

Festo valve for fast, reliable control of compressed-air direction and flow. The key technical data of this genuine Festo article are listed below.

Valve function	3/2 closed monostable
Actuation type	Mechanical
Normal nominal flow [l/min]	120
Operating pressure [bar]	3.5 to 8
Construction set up	Piston seat
Reset mode	Mechanical spring
Sealing principle	Soft
installation position	arbitrary
Control type	pilot operated
Flow direction	Not reversible
Information about force dynamic sampling	Switching frequency at least 1x per week

esd.equipment

Keldersstr. 15
42697 Solingen, Deutschland
VAT ID: DE269659389

Phone: +49 212 38340680
shop@esd-equipment.com

esd.equipment

Page 1/2

Operating medium	Compressed air to ISO8573-1:2010 [-:-:-]
Medium temperature [°C]	-10 to 60
ambient temperature [°C]	-10 to 60
actuating force [N]	8,00
Fastening type	With throughway bores
Pneumatic connection 1	G1/8
Pneumatic connection 2	G1/8
Pneumatic connection 3	G1/8
Material information	RoHs compliant
Cover material	POM
Seals material	NBR TPE-U(PU)
Housing material	Aluminium