

Front Panel Valve SVS-4-1/8 - Festo 10192

Item no. FES-10192

Manufacturer Festo

EAN 4052568009014

Festo valve for fast, reliable control of compressed-air direction and flow.

TECHNICAL DATA

Betriebsdruck max [bar]	8.000000
HS-Code	84812090
Pneumatischer Anschluss	G1/8
Weight	0.175 kg
Werkstoff	Aluminium



STANDARDS & COMPLIANCE

ISO8573-1:2010

DESCRIPTION

Festo valve for fast, reliable control of compressed-air direction and flow. The key technical data of this genuine Festo article are listed below.

Valve function	4/2 monostable
Actuation type	Mechanical
Normal nominal flow [l/min]	120
Operating pressure [bar]	3.5 to 8
Construction set up	Piston seat
Reset mode	Mechanical spring
Sealing principle	Soft
installation position	arbitrary
Control type	Direct
Flow direction	Not reversible
Operating medium	Compressed air to ISO8573-1:2010 [-:-:-]

ambient temperature [°C]	-10 to 60
actuating force [N]	8,00
Fastening type	With throughway bores
Pneumatic connection 1	G1/8
Pneumatic connection 2	G1/8
Pneumatic connection 3	G1/8
Cover material	POM
Seals material	NBR TPE-U(PU)
Housing material	Aluminium
Pneumatic connection 4	G1/8