

Quick Connector CK-3/8-PK-6 - Festo 2032

Item no. FES-2032

Manufacturer Festo

EAN 4052568000011

Festo fitting or line component for fast, leak-tight and pressure-resistant compressed-air connections.

TECHNICAL DATA

Corrosion resistance class CRC **2 - moderate corrosion stress**

HS-Code **76090000**

Material **Aluminium**

Medium **Compressed air, water**

Mounting position **arbitrary**

Nennweite DN [mm] **4,9**

Pneumatic connection **G3/8**

Series **CK**

Temperature (max.) **60**

Weight **0.012 kg**



STANDARDS & COMPLIANCE

ISO 8573-1:2010

DESCRIPTION

Festo fitting or line component for fast, leak-tight and pressure-resistant compressed-air connections. The key technical data of this genuine Festo article are listed below.

Nominal width [mm]	4,9
Seal type on stud	gasket
installation position	arbitrary
Pneumatic connection 1	Male thread G3/8
Pneumatic connection 2	For hose exterior diameter 8 mm
Material information	RoHs compliant
Housing material	Aluminium
Maritime classification	see Certificate
Operating medium	Compressed air to ISO 8573-1:2010 [7:-:-] Water according to manufacturer declaration at www.festo.com

Information about operating and control medium

Oiled operation possible

Corrosion resistant class KBK

2 - moderate corrosion stress

ambient temperature [°C]

-10 to 60