

Quick Connector CK-3/8-PK-6-KU - Festo 6460

Item no. FES-6460

Manufacturer Festo

EAN 4052568019846

Festo fitting or line component for fast, leak-tight and pressure-resistant compressed-air connections.

TECHNICAL DATA

Corrosion resistance class **2 - moderate corrosion stress**
CRC

HS-Code **39174000**

Material **POM**

Medium **Compressed air, water**

Mounting position **arbitrary**

Nennweite DN [mm] **5,3**

Pneumatic connection **G3/8**

Series **CK**

Temperature (max.) **60**

Weight **0.0075 kg**



STANDARDS & COMPLIANCE

ISO 8573-1:2010

DESCRIPTION

Festo fitting or line component for fast, leak-tight and pressure-resistant compressed-air connections. The key technical data of this genuine Festo article are listed below.

Nominal width [mm]	5,3
Seal type on stud	sealing edge
installation position	arbitrary
Pneumatic connection 1	Male thread G3/8
Pneumatic connection 2	For hose exterior diameter 8 mm
Material information	RoHs compliant
Housing material	POM
Maritime classification	see Certificate
Operating medium	Compressed air to ISO 8573-1:2010 [7:-:-] Water according to manufacturer declaration at www.festo.com
Information about operating and control medium	Oiled operation possible

esd.equipment

Keldersstr. 15
42697 Solingen, Deutschland
VAT ID: DE269659389

Phone: +49 212 38340680
shop@esd-equipment.com

esd.equipment

Page 1/2

Corrosion resistant class KBK	2 - moderate corrosion stress
ambient temperature [°C]	-10 to 60
Operating pressure complete temperature range [bar]	0 to 10