

Quick Connector CK-3/8-PK-9-KU - Festo 6468

Item no. FES-6468

Manufacturer Festo

EAN 4052568019853

Festo fitting or line component for fast, leak-tight and pressure-resistant compressed-air connections.

TECHNICAL DATA

HS-Code 39174000

Pneumatischer Anschluss G3/8

Weight 0.0091 kg

Werkstoff POM



STANDARDS & COMPLIANCE

ISO 8573-1:2010

DESCRIPTION

Festo fitting or line component for fast, leak-tight and pressure-resistant compressed-air connections. The key technical data of this genuine Festo article are listed below.

Nominal width [mm]	8,0
Seal type on stud	sealing edge
installation position	arbitrary
Pneumatic connection 1	Male thread G3/8
Pneumatic connection 2	For hose inside diameter 9 mm
Material information	RoHs compliant
Housing material	POM
Maritime classification	see Certificate
Operating medium	Compressed air to ISO 8573-1:2010 [7:-:-] Water according to manufacturer declaration at www.festo.com
Information about operating and control medium	Oiled operation possible

esd.equipment

Keldersstr. 15
42697 Solingen, Deutschland
VAT ID: DE269659389

Phone: +49 212 38340680
shop@esd-equipment.com

esd.equipment

Page 1/2

Corrosion resistant class KBK	2 - moderate corrosion stress
ambient temperature [°C]	-10 to 60
Operating pressure complete temperature range [bar]	0 to 10