

Barbed Fitting CRCN-M5-PK-3 - Festo 13967

Item no.	FES-13967	Manufacturer	Festo
Manufacturer no.	CRCN-M5-PK-3	EAN	4052568021627

Festo fitting or line component for fast, leak-tight and pressure-resistant compressed-air connections.

TECHNICAL DATA

Article authenticity	Original product
Condition of article	New
HS-Code	73072910
Pneumatischer Anschluss	M5
Weight	0.002 kg
Werkstoff	Edelstahl



STANDARDS & COMPLIANCE

ISO 8573-1:2010

DESCRIPTION

Festo fitting or line component for fast, leak-tight and pressure-resistant compressed-air connections. The key technical data of this genuine Festo article are listed below.

Nominal width [mm]	2,5
Seal type on stud	gasket
Operating pressure complete temperature range [bar]	-0.95 to 10
Operating medium	Compressed air to ISO 8573-1:2010 [7:-:-]
Information about operating and control medium	Oiled operation possible (required in further operations)
Corrosion resistant class KBK	2 - moderate corrosion stress
ambient temperature [°C]	0 to 60
Pneumatic connection 1	Male thread M5
Pneumatic connection 2	For hose exterior diameter 4 mm
Material information	RoHs compliant

Housing material
Packing size
Food compatibility
Product weight [g]
Thread sealing material

High-alloyed stainless steels
10
See expanded material information
1,74
NBR
hochlegierter Stahl rostfrei