

Quick Coupling Plug KS4-1/4-A-R - Festo 531677

Item no. FES-531677

Manufacturer Festo

EAN 4052568047887

Festo fitting or line component for fast, leak-tight and pressure-resistant compressed-air connections.

TECHNICAL DATA

Corrosion resistance class CRC **1 - low corrosion stress**

Durchfluss [l/min] **765**

HS-Code **74122000**

Medium **Druckluft**

Nennweite DN [mm] **8**

Pneumatischer Anschluss **G1/4**

Serie **KS4**

Temperature (max.) **60**

Weight **0.047 kg**



STANDARDS & COMPLIANCE

ISO 8573-1:2010

DESCRIPTION

Festo fitting or line component for fast, leak-tight and pressure-resistant compressed-air connections. The key technical data of this genuine Festo article are listed below.

Nominal width [mm]	8,00
Operating pressure complete temperature range [bar]	-0.95 to 12
Normal nominal flow [l/min]	765
Operating medium	Compressed air to ISO 8573-1:2010 [7:-:-]
Information about operating and control medium	Oiled operation possible
Corrosion resistant class KBK	1 - low corrosion stress
ambient temperature [°C]	-10 to 60
Product weight [g]	46,0
Pneumatic connection 1	Male thread G1/4
Material information	RoHs compliant
Nominal tightening torque [Nm]	9,50

Tolerance to nominal tightening torque

$\pm 15 \%$
